

Window Film Performance Data

**Legend™**

**leg•end** |lɛg'ɛnd| remarkable, one that inspires.

Utilizing the latest technology in spectrally selective materials and Titanium Nitrite sputtering processes. Superior solar heat rejection, over 99% UV blocking and unparalleled looks while being “signal-friendly.”

**Excel™**

**ex•cel** |ɪk'sɛl'| to do better than, to surpass.

The Excel™ series surpasses as a non-reflective film. A black color stable dyed film that gives the consumer and the professional a durable choice for a lifetime.

**Performer™**

**per•form•er** |pɜr'fɔr'mɛr| something that takes action from the requirements, to fulfill.

The Performer™ series does just that — it performs. A high-performance auto film with a color-stable non-reflective dyed film, and a layer of metallized film, this series provides good looks and high heat rejection.

**Impulse™**

**im•pulse** |ɪm'pʊls'| an impelling action or force, driving onward.

The Impulse™ series is a high performance film comprised of a deep dyed charcoal film and a reflective metallized layer that delivers good looks and comfort.

**Metallic™**

**me•tal•lic** |mɪ'tal'ɪk| a material displaying a lustrous appearance

The Metallic™ series is a metallic automotive film that provides maximum heat rejection and a rich, glossy look. An unparalleled lifetime warranty means this film will look cool — and keep you cool.

**Retro™**

**ret•ro** |rɛt'rɔ| reviving of things past

The Retro™ series celebrates the nostalgic style of the past, with advancements for today! A non-reflective film with classic looks, it offers cutting-edge technological improvements for clarity and ease of use.

**Dimension™**

**di•men•sion** |dɪ'mɛn'shən| a measure of spacial extent

Dimension™ uses the latest generation ceramic nano-particulate technology which delivers a spectrally selective product with high heat rejection while remaining nearly transparent.

	Light Transmission	Solar Energy Rejected	U/V Rejected	Construction Ply/Thickness	Visible Light Reflectance Interior	Visible Light Reflectance Exterior
15	15%	61%	99%	1.5 M 2 ply	7%	11%
25	23%	58%	99%	1.5 M 2 ply	7%	11%
40	38%	57%	99%	1.5 M 2 ply	10%	10%
50	52%	57%	99%	1.5 M 2 ply	15%	12%

5	7%	50%	99%	1.5 M 2 ply	5%	5%
15	16%	44%	99%	1.5 M 2 ply	5%	5%
20	22%	39%	99%	1.5 M 2 ply	5%	5%
30	30%	38%	99%	1.5 M 2 ply	5%	5%
35	35%	37%	99%	1.5 M 2 ply	5%	5%
50	50%	35%	99%	1.5 M 2 ply	5%	5%
60	61%	33%	99%	1.5 M 2 ply	5%	5%
70	68%	25%	99%	1.5 M 2 ply	5%	5%
88	88%	18%	99%	1.5 M 2 ply	5%	5%

3	4%	66%	99%	1.5 M 3 ply	9%	6%
5	6%	57%	99%	1.5 M 2 ply	8%	6%
15	16%	56%	99%	1.5 M 2 ply	11%	8%
20	19%	54%	99%	1.5 M 2 ply	11%	8%
30	30%	51%	99%	1.5 M 2 ply	11%	8%
35	37%	50%	99%	1.5 M 2 ply	11%	8%
50	55%	39%	99%	1.5 M 2 ply	11%	8%
60	65%	33%	99%	1.5 M 2 ply	11%	8%

5	5%	58%	99%	1.5 M 2 ply	8%	6%
15	16%	54%	99%	1.5 M 2 ply	11%	8%
20	20%	53%	99%	1.5 M 2 ply	11%	8%
30	29%	45%	99%	1.5 M 2 ply	7%	6%
35	38%	49%	99%	1.5 M 2 ply	11%	8%
50	50%	39%	99%	1.5 M 2 ply	11%	8%

10	10%	60%	99%	1.5 M 2 ply	5%	12%
20	18%	57%	99%	1.5 M 2 ply	6%	12%
35	35%	53%	99%	1.5 M 2 ply	13%	13%
50	54%	50%	99%	1.5 M 2 ply	9%	9%

5	5%	50%	99%	1.5 M 2 ply	5%	5%
15	13%	40%	99%	1.5 M 2 ply	5%	5%
20	22%	39%	99%	1.5 M 2 ply	5%	5%
35	35%	38%	99%	1.5 M 2 ply	5%	5%
50	51%	35%	99%	1.5 M 2 ply	5%	5%

80	79%	36%	99%	1.5 M 2 ply	9%	9%
----	-----	-----	-----	-------------	----	----